

Safety Data Sheet

according to 2001/58/EC

RUDOL LASTIC

Print date : 13.12.2006

Product code : 1620

Page 1 of 6

1. Identification of the substance/preparation and of the company/undertaking**1.1 Identification of the substance or preparation**

RUDOL LASTIC

Use of the substance/preparation

Adhesive

1.2 Company/undertaking identification

Company name : RUDOL-FABRIK Hermann Hagemeyer

Street : Sürther Str. 172

Place : D-50321 Brühl

Post-office box : 17 04

D-50307 Brühl

Contact person : Klaus Markus

Telephone : 02232-94592-0

Telefax : 02232-945929

Inquiry office : Labor

Emergency telephone : 02232-945920

2. Composition/information on ingredients**Chemical characterization (preparation)**

Kunstharzkleber

Hazardous components

EC-No.	CAS-No.	Chemical name	Quantity	Classification
205-500-4	141-78-6	Ethylacetat	40-45%	F, Xi R11-36-66-67
200-662-2	67-64-1	Aceton	8-12%	F, Xi R11-36-66-67
265-151-9	64742-49-0	Naphta, mit Wasserstoff behandelt leicht, <0,1 Benzol	8-12%	F, Xn, Xi, N R11-38-51-53-65-67
201-159-0	78-93-3	Butanon (vgl. Ethylmethylketon)	9%	F, Xi R11-36-66-67
204-658-1	123-86-4	n-Butylacetat	2%	R10-66-67

Full text of each relevant R phrase can be found in heading 16.

3. Hazards identification**Classification**

Symbols : Highly flammable, Irritant

R-phrases :

Highly flammable.

Irritating to eyes.

Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Explication of special hazards for human health and environment

In use, may form flammable/explosive vapour-air mixture.

4. First aid measures**After inhalation**

Move to fresh air in case of accidental inhalation of vapours. If symptoms persist, call a physician.

After contact with skin

Wash off immediately with soap and plenty of water.

Safety Data Sheet

according to 2001/58/EC

RUDOL LASTIC

Print date : 13.12.2006

Product code : 1620

Page 2 of 6

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

After ingestion

Do NOT induce vomiting. Consult a physician.

5. Fire-fighting measures**Suitable extinguishing media**Dry chemical Carbon dioxide (CO₂) Extinguishing media - large fires Water spray mist or foam. In the event of fire and/or explosion do not breathe fumes.**Extinguishing media which must not be used for safety reasons**

Do not use a solid water stream as it may scatter and spread fire.

Special exposure hazards arriving from substance or preparation itself, combustion products, resulting gases

Using the product may be accompanied by the formation of explosive/highly inflammable vapour-air-mixtures. Use water spray to cool unopened containers.

Special protective equipment for fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary.

6. Accidental release measures**Personal precautions**

Keep people away from and upwind of spill/leak. Ensure adequate ventilation.

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Methods for cleaning up/taking up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Additional information

Remove all sources of ignition.

7. Handling and storage**7.1 Handling****Advice on safe handling**

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Further information on handling

Provide sufficient air exchange and/or exhaust in work rooms. Do not smoke.

7.2 Storage**Requirements for storage rooms and vessels**

Keep container tightly closed in a dry and well-ventilated place.

8. Exposure controls/personal protection**8.1 Exposure limit values**

Safety Data Sheet

according to 2001/58/EC

RUDOL LASTIC

Print date : 13.12.2006

Product code : 1620

Page 3 of 6

Exposure limits (EH40)

CAS No.	Substance	ml/m ³	mg/m ³	F/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL

BAT values (TRGS 903)

CAS No.	Substance	Value	Parameter	Test material	Sampling time
78-93-3	2-Butanon (Ethylmethylketon)	5 mg/l	2-Butanon	U	b
67-64-1	Aceton	80 mg/l	Aceton	U	b

8.2 Exposure controls**Occupational exposure controls**

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Avoid contact with the skin and the eyes. Remove and wash contaminated clothing before re-use.

Wash hands before breaks and at the end of workday.

Respiratory protection

Ensure adequate ventilation, especially in confined areas. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Eye protection

Tightly fitting safety goggles

9. Physical and chemical properties**9.1 General information**

Physical state : liquid
 Colour : clear
 Odour : solvent

9.2 Important health, safety and environmental information

Test method

Changes in the physical state

Boiling point : 80 °C
 Flash point : - 6 °C
 Lower explosion limits : 1,4 vol. %
 Upper explosion limits : 11,8 vol. %
 Vapour pressure : 300 hPa
 (at 20 °C)
 Density (at 20 °C) : 0,90 g/cm³
 Water solubility : partly soluble
 (at 20 °C)
 Solubility in other solvents : ester, ketone

Safety Data Sheet

according to 2001/58/EC

RUDOL LASTIC

Print date : 13.12.2006

Product code : 1620

Page 4 of 6

Viscosity / dynamic : 300 mPa·s
(at 20 °C)

Solvent content
75%

9.3 Other information

Ignition temperature : >200 °C

10. Stability and reactivity**Conditions to avoid**

Risk of decomposition.:
No decomposition if used as directed.

Hazardous decomposition products

No dangerous reaction known under conditions of normal use.

Additional information

No decomposition if stored normally.

11. Toxicological information**Specific effects in experiment on an animal**

Eye/rabbit = Mild eye irritation

Sensitising effects

Sensitization: Sensitization: no sensitizing effect known.

12. Ecological information**Ecotoxicity**

Do not allow to escape into waters, wastewater or soil.

Mobility

The product evaporates readily.

13. Disposal considerations**Advice on disposal**

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances
Classified as hazardous waste.

Contaminated packaging

Fully drained containers which are drop- and scrape-free can be treated as industrial waste, and can possibly be recycled.

14. Transport information**Land transport (ADR/RID)**

ADR/RID class : 3
Warning plate
Hazard-no. : 33
UN number : 1133
Hazard label : 3

Safety Data Sheet

according to 2001/58/EC

RUDOL LASTIC

Print date : 13.12.2006

Product code : 1620

Page 5 of 6

ADR/RID packing group : III

Description of the goods

adhesive

Remarks (land transport)

Sondervorschrift 640H

Inland waterways transport

ADN/ADNR class : 3
 Category : F1
 UN number : 1133

Description of the goods

Klebstoffe

Remarks (inland waterways transport)

Sondervorschrift 640H

Marine transport

IMDG code : 3
 UN number : 1133
 Marine pollutant : -
 EmS : F-E, S-D
 IMDG packing group : III
 Hazard label : 3

Description of the goods

adhesive

Air transport

ICAO/IATA-DGR : 3
 UN/ID number : 1133
 Hazard label : 3
 IATA-packing instructions - Passenger : 309
 IATA-max. quantity - Passenger : 60 L
 IATA-packing instructions - Cargo : 310
 IATA-max. quantity - Cargo : 220 L
 ICAO packing group : III

Description of the goods

Adhesives

15. Regulatory information**15.1 Labelling**

Indication of danger : F - Highly flammable; Xi - Irritant
 Labelling according to EC-guidelines : Labelling in accordance with the EEC directives:

R phrases

11 Highly flammable.
 36 Irritating to eyes.
 66 Repeated exposure may cause skin dryness or cracking.
 67 Vapours may cause drowsiness and dizziness.
 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S phrases

02 Keep out of the reach of children.
 09 Keep container in a well-ventilated place.
 16 Keep away from sources of ignition - No smoking.
 23 Do not breathe Gas/Rauch/Dampf/Aerosol.

Safety Data Sheet

according to 2001/58/EC

RUDOL LASTIC

Print date : 13.12.2006

Product code : 1620

Page 6 of 6

- 29 Do not empty into drains.
33 Take precautionary measures against static discharges.

15.2 National regulations

Water contaminating class : 1 - slightly water contaminating
1999/13/EC (VOC) : 75%

16. Other information**List of relevant R phrases**

- 10 Flammable.
11 Highly flammable.
36 Irritating to eyes.
38 Irritating to skin.
51 Toxic to aquatic organisms.
53 May cause long-term adverse effects in the aquatic environment.
65 Harmful: may cause lung damage if swallowed.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Other data

The data given here is based on current knowledge and experience. The purpose of this Safety Data Sheet is to describe the products in terms of their safety requirements. The data does not signify any warranty with regard to the products' properties.